

- High efficiency, low UGR LED panel.



FEATURES

- Super slim design
- Extruded aluminium frame
- Powder coated finish
- Opal polystyrene diffuser
- Edge lit
- UGR < 19
- Low colour temperature variance: SDCM ≤ 4

INCLUDES

- High efficiency LED panel light
- Constant current LED driver
- DALI driver compatible
- 1.2 m flex and plug

INSTALLATION OPTIONS

- Standard metric T-bar ceiling recessed installation
- Suspended (Suspension kit is required)
- Recessed plaster ceiling installation (Plaster frame is required)
- Surface mounting installation (Surfaced mounted frame is required)

APPLICATIONS

- Offices and conference rooms
- Schools and retail

WARRANTY

- Five years (subject to terms and conditions)

CERTIFICATION	IP RATING	DIMMABLE	SDCM	Ra	DISTRIBUTION	DIMENSIONS(mm)
			SDCM ≤ 4			

Part No.	Voltage	Watt.	PF	Color Temp.	Lumens	Beam Angle	Lifetime L70B50	Lifetime L70B10	Size(L*W*H)mm	Net Weight (kg)
222407	100-240V	18W	0.9	4000K	1500lm	85°	50000h	35000h	595*295*10	1.23
222408A	100-240V	36W	0.9	4000K	3600lm	85°	50000h	35000h	595*595*10	2.15
222409A	100-240V	36W	0.9	4000K	3600lm	85°	50000h	35000h	1195*295*10	2.18

Part No.	Model No.	VEET Status	IPART Status
222407	YKPLA3G1U-R60x30 WT	Approved VEET No.: 5239	Approved IPART No.: 24143D15-JIGIFFEF
222408A	PLA3G1U-R60x60	Approved VEET No.: 7113	Approved IPART No.: 24143S15-TVDIHG1
222409A	PLA3G1U-R120x30	Approved VEET No.: 7113	Approved IPART No.: 24143S15-TVDIHG1

[1] Operating Frequency=50/60Hz;

[2] Operating Temperature:-20 °C ~ +40 °C ;

[3] Other temperature, 0-10V dimmable, DALI dimmable and no flickr options are available on request, subject to MOQ