



4K 5K 6.5K

The Baklite Tri-Colour backlit LED Panel is an affordable lighting solution with 4 sizes in the range.

Tri-Colour temperatures of 4K/5K/6.5K and multiple wattages of 17W/32W/50W in one

product make this the ultimate panel suitable for a variety of applications. The luminaire has low energy consumption but high lumen efficiency of 100Lm/W, and its flicker free feature helps eye discomfort. Perfect for office environments.

Baklite Tri LED Panel

Backlit LED Panel



Features

- Extruded aluminium frame
- Powder coated finish
- Back lit with 0.9M Flex&Plug
- UGR<22

Applications

Offices, Conference rooms Schools, Retail

595*295 595*595 1195*295 1195*595

Warranty

3 years



























Product Data

Order Code	Wattage	сст	Lumen Output	Beam Angle	Inrush Current	Inrush Time	Size (LxWxH)mm	Weight (kg)
221019	17W	4K / 5K / 6.5K	1600/1700/1600Lm	110°	27A	100uS	595*295*33	0.95
221020	32W	4K / 5K / 6.5K	3200/3400/3200Lm	110°	44.8A	117.7uS	595*595*33	1.52
221021	32W	4K / 5K / 6.5K	3200/3400/3200Lm	110°	44.8A	117.7uS	1195*295*33	1.60
221022	50W	4K / 5K / 6.5K	5000/5100/5000Lm	110°	17A	300uS	1195*595*33	3.32

[1] Operating temperature: $-20^{\circ}\text{C} \sim +40^{\circ}\text{C}$

[2] Voltage: 220-240V

[3] PF: 0.9