

SUMMARY

The Baklite is an LED back-lit panel solution for commercial applications. Engineered to be slim for easy handling and installation, it's only 33mm thin. It features high efficiency SMD LED chips and a remote Flicker-Free driver for ocular health and cognitive wellbeing. It also features a pre-wired flex and plug for quick and easy installation. Rated to IP54, it has a CRI rating of Ra>80 and a MacAdams rating of SDCM<4. Built to last, it has a metal frame and opal polycarbonate diffuser. This product is HEERS approved.



			<ul style="list-style-type: none"> VEET Approved IPART Approved HEERS Approved
--	--	--	---

PRODUCT DATA

Order Code	223574
Voltage	220-240V
Wattage	25W
Lumen Output	3000Lm
CCT	4000K
IP Rating	IP40
UGR Rating	UGR<22
MacAdams Rating	SDCM≤4
CRI Rating	Ra≥80
Beam Angle	110°
Light Source	SMD Chips
Driver	Remote Flicker-Free
Dimmable	No
Connection	1.2 flex and plug
Construction	Metal frame / Opal polycarbonate diffuser
Finish	Powder coated
Fitting Colour	White
PF	0.9
Net Weight (kg)	1.70
Lifetime L70B50	50,000 hours
Warranty	3 years

