



CANOLITE

RESSESSED CANOPY

Canolite Canopy is designed with high efficacy up to 150Lm/W. It's typically used for illuminating building entrances, gas station canopies, parking garages or any other covered areas.

It comes with Tri-colour and multi-watt for temperature and wattage adjustment to suit a variety of needs.

Canolite has a simple and clean appearance, the Aluminium heat sink and tempered glass provide the fitting with robust protection against damage from impacts or other external factors.

Available in either recessed or surface mount providing versatility for multiple installations.

Features

- Die-cast Aluminium with excellent thermal management
- Tempered glass cover
- Pre-wired 1.5m flex & plug
- Recessed kit included
- Microwave dimming sensor option available
- 0-10V, DALI option available





Applications

Warehouse, service stations and car parks

Warranty

5 years



Product Data

Order Code	Wattage	CCT	Lumen Output	Beam Angle	Size (LxWxH)mm	Weight (kg)
371018	75/100/120/150W	3000K/4000K/5000K	11250Lm/15000Lm/18000/22500Lm	120°	400x400x79	5.5

[1] Operating temperature: -30°C~+50°C

[2] Voltage: 220-240V

[3] PF: 0.90

[4] Inrush Current: 90A @ 300µs

Optional Accessories

Description	Order Code
Surface Mount Kit White	373189
U Bracket White	373199

Specifications are for reference only and may be changed without prior notice.