



control or add a range of reflectors for different

distribution requirements.

efficiency of up to 175 lumens per watt, this

efficiency.

luminaire provides powerful illumination and energy



## **Features**

- Tri-CCT 3000K/4000K/5000K selectable
- Multi-Watt up to 200W
- High lumen efficiency up to 175Lm/W
- Die-cast Aluminium heat sink, high efficiency heat dissipation
- Highly transparent clear polycarbonate lens
- Plug-in Microwave sensor optional
- DALI 2.0 optional



- Suspension installation
- Surface mount installation (surface mounting kits are required)
- Pole installation (Brackets are required )



Workshops, Warehouses, Industrial, Commercial Facilities, fitness centers

























## **Product Data**

Order Code	Wattage	ССТ	Lumen Output	Beam Angle	Inrush Current		PF	Size (DxH)mm	Weight (kg)
331001	150/120/100/70W	3K / 4K / 5K	26250/21000/17000/12250lm@4K	110°	61A	157uS	0.9	300*164	2.3
331002	200/180/150/120W	3K / 4K / 5K	35500/31500/26250/21000lm@4K	110°	68A	213uS	0.9	360*164	3.0

## **Optional Accessories**

Item	Order Code	
Plug-in Microwave sensor	333749	
Remote Controller of Senser	213979	
Surface mounted bracket for Falcon, Hilux Highbay	333589	
Pole Mounting bracket for Falcon, Hilux Highbay	333609	

[1]	Tri-Colour	Selectable	options

- 3K @ 160Lm/W 4K @ 175Lm/W 5K @ 170Lm/W
- [2] Voltage: 220-240V
- [3] Operating Frequency = 50Hz;
- [4] Operating Temperature: -30  $^{\circ}\text{C} \sim \!\!+50 \,^{\circ}\text{C}$
- [5] Earth leakage current: <0.7mA
- [6] SDCM<4 is only applicable for 3000K and 5000K









Item for 331001	Order Code
90° Highbay Reflector	333199
70° Highbay Reflector	333259
70° Highbay Diffuser	333319

Item for 331002	Order Code	
70° PC Diffuser	333809	