



SUMMARY

The Legolite is a high performing commercial downlight. Engineered to deliver high lumen efficacy, it features Tri-Colour Selectable technology, giving installers a choice of 3 colour temperatures within 1 fitting for individual preference or application requirements. Incorporating an integrated dimmable driver, it also features Multi-Watt Selectable technology, giving installers a choice of 2 wattages within 1 fitting for maximum lumen output flexibility.











PRODUCT DATA

Order Code	263006	263006	
Voltage	220-240V	220-240V	
Wattage	Multi-Watt Se	Multi-Watt Selectable	
	25W	18W	
Lumen Output 3K	2150Lm	1650Lm	
Lumen Output 4K & 5K	2300Lm	1800Lm	
ССТ	Tri-Colour Se	Tri-Colour Selectable - 3K / 4K / 5K	
IP Rating	IP54	IP54	
IC Rating	CA90	CA90	
Beam Angle	110°	110°	
Light Source	SMD Chips	SMD Chips	
Driver	Integrated	Integrated	
Dimmable	Yes. Leading	Yes. Leading or Trailing Edge, Universal	
	(Refer to Dim	(Refer to Dimmer Compatibility List)	
Connection	1.2m flex & p	1.2m flex & plug	
Cutout Size	Ø150mm	Ø150mm	
Construction	Polycarbonat	Polycarbonate body / opal polycarbonate diffuser	
Fitting Colour	White	White	
PF	0.9	0.9	
Net Weight (kg)	0.60	0.60	
Lifetime L70B50	50,000 hours	50,000 hours	
Warranty	5 years	5 years	

















