


SUMMARY

The Stellar V is an IP20 batten ideal for commercial and industrial applications. It features Five-Colour selectable and Multi-Watt selectable technologies, giving installers the choice of 5 colour temperatures and 8 wattages in 1 fitting so that fewer varieties are required to meet a broader range of needs. With the installer in mind, the Stellar V has been engineered with a clever toolless end cap and quick-to-fit single piece LED light module. It also incorporates multiple cable entry points and a large 6mm terminal block. The integrated sensor's dimming function can be conveniently controlled from a distance with the compatible remote control - available to order separately. Fully approved to AS/NZS-2293.



PRODUCT DATA

Order Code	211024DEMS							
Voltage	220-240V							
Wattage	Multi-Watt Selectable							
	40W	36W	30W	26W	24W	20W	14W	10W
Lumen Output 3K	3600Lm	3240Lm	2700Lm	2340Lm	2160Lm	1800Lm	1260Lm	900Lm
Lumen Output 4K, 5K, 5.7K & 6.5K	4000Lm	3600Lm	3000Lm	2600Lm	2400Lm	2000Lm	1400Lm	1000Lm
CCT	Five-Colour Selectable - 3K / 4K / 5K / 5.7K / 6.5K							
IP Rating	IP20							
Beam Angle	120°							
Light Source	SMD Chips							
Driver	Integrated							
Dimmable	Yes. 0-10V							
Construction	Metal body / opal polycarbonate diffuser							
Fitting Colour	White							
PF	0.9							
EMG Classification	C0:D50 / C90:D40							
Battery	LiFePO4							
Net Weight (kg)	2.20							
Lifetime L70B50	50,000 hours							
Warranty	3 years							

OPTIONAL ACCESSORIES

ITEM	ORDER CODE
Remote Control	213979

