



IP65 Floodlight

SUMMARY

The SupValite V is a floodlight solution for residential applications. It features Five-Colour and Multi-Watt selectable technologies offering the flexibility and convenience of 5 colour temperatures and 2 wattages in 1 fitting, allowing installers to cater to a broader range of needs with fewer variants. Rated IP65 and IK08, it is perfectly suited to harsh outdoor conditions.











PRODUCT DATA

Order Code	271000	271000	
Voltage	220-240V	220-240V	
Wattage	Multi-Watt Se	Multi-Watt Selectable	
	30W	20W	
Lumen Output 3K	3000Lm	2000Lm	
Lumen Output 4K, 5K, 5.7K & 6.5K	3000Lm	2000Lm	
ССТ	Five-Colour S	Five-Colour Selectable - 3K / 4K / 5K / 5.7K / 6.5K	
IP Rating	IP65	IP65	
IK Rating	IK08	IK08	
CRI Rating	Ra≥80	Ra≥80	
Beam Angle	110°	110°	
Light Source	SMD Chips	SMD Chips	
Driver	Integrated	Integrated	
Dimmable	No	No	
Connection	1.2m flex & p	1.2m flex & plug	
Construction	Aluminium bo	Aluminium body / tempered etched glass diffuser	
Fitting Colour	Black	Black	
PF	0.9	0.9	
Net Weight (kg)	0.67	0.67	
Lifetime L70B50	50,000 hours	50,000 hours	
Warranty	5 years	5 years	













