

**SUMMARY**

The Tempest V is a robust IP65 weatherproof batten ideal for industrial and commercial applications. It features Five-Colour Selectable technology; a first-to-market innovation that gives installers the choice of 5 colour temperatures within 1 fitting for individual preference or application requirements. It also features Multi-Watt Selectable technology, giving you a choice of 8 wattages within 1 fitting for maximum lumen output flexibility. Built tough for high vandalism areas, the Tempest V incorporates a high impact diffuser, stainless steel clips and a quick-to-fit one-piece sealed LED light module. Fully approved to AS/NZS-2293, the integrated sensor's dimming function can be conveniently controlled from a distance with the optionally available remote control.



|  |  |  |  |
|--|--|--|--|
|  |  |  | <p>✓ <b>VEET</b><br/>Approved</p> <p>✓ <b>IPART</b><br/>Approved</p> |
|--|--|--|--|

**PRODUCT DATA**

|                                  |  |        |        |        |        |        |        |        |
|----------------------------------|--|--------|--------|--------|--------|--------|--------|--------|
| Order Code                       | 211022DEMS   |        |        |        |        |        |        |        |
| Voltage                          | 220-240V   |        |        |        |        |        |        |        |
| Wattage                          | Multi-Watt Selectable  |        |        |        |        |        |        |        |
|                                  | 40W  | 36W    | 30W    | 26W    | 24W    | 20W    | 14W    | 10W    |
| Lumen Output 3K                  | 3720Lm   | 3348Lm | 2790Lm | 2418Lm | 2232Lm | 1860Lm | 1302Lm | 930Lm  |
| Lumen Output 4K, 5K, 5.7K & 6.5K | 4000Lm   | 3600Lm | 3000Lm | 2600Lm | 2400Lm | 2000Lm | 1400Lm | 1000Lm |
| CCT                              | Five-Colour Selectable - 3K / 4K / 5K / 5.7K / 6.5K          |        |        |        |        |        |        |        |
| IP Rating                        | IP65   |        |        |        |        |        |        |        |
| IK Rating                        | IK08   |        |        |        |        |        |        |        |
| Beam Angle                       | 120°   |        |        |        |        |        |        |        |
| Light Source                     | SMD Chips  |        |        |        |        |        |        |        |
| Driver                           | Integrated   |        |        |        |        |        |        |        |
| Dimmable                         | Yes. 0-10V   |        |        |        |        |        |        |        |
| Construction                     | High impact polycarbonate body / opal polycarbonate diffuser |        |        |        |        |        |        |        |
| Fitting Colour                   | Grey   |        |        |        |        |        |        |        |
| PF                               | 0.9  |        |        |        |        |        |        |        |
| EMG Classification               | C0:D63 / C90:D32   |        |        |        |        |        |        |        |
| Battery                          | LiFePO4  |        |        |        |        |        |        |        |
| Net Weight (kg)                  | 2.42   |        |        |        |        |        |        |        |
| Lifetime L70B50                  | 50,000 hours   |        |        |        |        |        |        |        |
| Warranty                         | 3 years  |        |        |        |        |        |        |        |

**OPTIONAL ACCESSORIES**

| ITEM                       | ORDER CODE | ITEM           | ORDER CODE |
|----------------------------|------------|----------------|------------|
| S316 Stainless Steel Clips | 232005     | Remote Control | 213979     |

