

**Tempest V** 

5 YEAR

5ft IP65 Batten

## SUMMARY

The Tempest V is a robust IP65 weatherproof batten ideal for industrial and commercial applications. It features Five-Colour Selectable technology; a first-to-market innovation that gives installers the choice of 5 colour temperatures within 1 fitting for individual preference or application requirements. It also features Multi-Watt Selectable technology, giving you a choice of 5 wattages within 1 fitting for maximum lumen output flexibility. Built tough for high vandalism areas, the Tempest V incorporates a high impact diffuser, stainless steel clips and a quick-to-fit one-piece sealed LED light module.



| 1565mm           |  |
|------------------|--|
| 115mm<br>I↓<br>O |  |

## **PRODUCT DATA**

| Order Code                       | 211033   |        |        |        |        |        |
|----------------------------------|--|--------|--------|--------|--------|--------|
| Voltage                          | 220-240V   |        |        |        |        |        |
| Wattage                          | Multi-Watt Selectable  |        |        |        |        |        |
| -                                | 60W  | 53W    | 48W    | 40W    | 36W    | 28W    |
| Lumen Output 3K                  | 5580Lm   | 4929Lm | 4464Lm | 3720Lm | 3348Lm | 2604Lm |
| Lumen Output 4K, 5K, 5.7K & 6.5K | 6000Lm   | 5300Lm | 4800Lm | 4000Lm | 3600Lm | 2800Lm |
| ССТ                              | Five-Colour Selectable - 3K / 4K / 5K / 5.7K / 6.5K          |        |        |        |        |        |
| IP Rating                        | IP65   |        |        |        |        |        |
| IK Rating                        | IK08   |        |        |        |        |        |
| Beam Angle                       | 120°   |        |        |        |        |        |
| Light Source                     | SMD Chips  |        |        |        |        |        |
| Driver                           | Integrated Flicker-Free                                      |        |        |        |        |        |
| Dimmable                         | Non-Dim  |        |        |        |        |        |
| Construction                     | High impact polycarbonate body / opal polycarbonate diffuser |        |        |        |        |        |
| Fitting Colour                   | Grey   |        |        |        |        |        |
| PF                               | 0.9  |        |        |        |        |        |
| Net Weight (kg)                  | 2.48   |        |        |        |        |        |
| Lifetime L70B50                  | 50,000 hours   |        |        |        |        |        |
| Warranty                         | 5 years  |        |        |        |        |        |

FLICKER

FREE

**CRI 80** 

## **OPTIONAL ACCESSORIES**

FIVE COLOUR

| ITEM                       | ORDER CODE |  |  |  |
|----------------------------|------------|--|--|--|
| S316 Stainless Steel Clips | 232005     |  |  |  |

IP65

IK08

MULTI WATT