



# UniGlow

## Industrial Lowbay

The UniGlow LED Lowbay has been designed to provide high quality lighting in large challenging environment areas and ceiling heights between 3.5m to 6m. With a High CRI90, UniGlow Lowbay ensures optimal colour rendering and visual clarity. Its robust construction boasts an IK10 rating for

impact resistance and IP65 protection against environmental elements. Flicker free is incorporated to minimize eye strain for extended usage. Available for surface mounting or with additional frame for recessed mount. Multi-Watt from 120w to 240w is standard.


### Features

- CRI90 ensuring optimal visual clarity and vividness
- IK10 and IP65 rating ensures durability and protection against impact and environmental elements
- Comfortable and stable lighting with Flicker-free technology, reducing eye strain
- Super high efficiency up to 140Lm/W
- 0-10V and DALI options available




### Applications

- Warehouses, cool rooms, car parks, service stations, clean room, hospitality, food preparation areas



Recessed Mounting



Surface Mounting

### Products Data

Order Code	Wattage	CCT	Lumen Output	Size(LxWxH)mm	Stock Type
373253	240W/200W/160W/120W	3000K	Upto 30240Lm	600*600*138mm	MTO
373254	240W/200W/160W/120W	4000K	Upto 33600Lm	600*600*138mm	ACTIVE
373263	40W	3000K	5040Lm	600*600*138mm	MTO
373264	40W	4000K	5600Lm	600*600*138mm	MTO
373214DALI	120W	4000K	16800Lm	600*600*138mm	MTO
373224DALI	160W	4000K	22400Lm	600*600*138mm	MTO
373234DALI	200W	4000K	28000Lm	600*600*138mm	MTO
373244DALI	240W	4000K	33600Lm	600*600*138mm	MTO

[1] Voltage: 220~240V

[2] Operating Frequency: 50/60Hz

[3] Operating Temperature: -25°C to +45°C

[4] 3000K – 126Lm/W and 4000K – 140Lm/W

### Accessories

Order Code	Description
373209	UniGlow Lowbay Frame For Recessed Installation

