

SUMMARY

The Unit is an IP66 bunker ideal for commercial and residential applications. It features Tri-Colour and Multi-Watt selectable technologies, giving installers a choice of 3 colour temperatures and 3 wattages within 1 fitting. Rated IK10, suitable for high vandalism areas, it has a high impact polycarbonate enclosure that is corrosion and UV resistant. Multiple cable entry points, a large 6mm terminal block and compatibility to 51mm Beza boxes facilitates quick and easy installation.



			<p>✓ VEET Approved</p> <p>✓ IPART Approved</p>
--	--	--	--

PRODUCT DATA

Order Code	281004		
Voltage	220-240V		
Wattage	Multi-Watt Selectable		
	22W	15W	10W
Lumen Output 3K	1860Lm	1400Lm	930Lm
Lumen Output 4K & 5K	2000Lm	1500Lm	1000Lm
CCT	Tri-Colour Selectable - 3K / 4K / 5K		
IP Rating	IP66		
IK Rating	IK10		
CRI Rating	Ra≥80		
Beam Angle	110°		
Light Source	SMD Chips		
Driver	Integrated Flicker-Free		
Dimmable	No		
Construction	Polycarbonate body / opal polycarbonate diffuser		
Fitting Colour	White		
PF	0.9		
EMG Classification	C0-C180:D32 / C90-C270:D32 (with emergency kit installed)		
Net Weight (kg)	0.82		
Lifetime L70B50	50,000 hours		
Warranty	5 years		

OPTIONAL ACCESSORIES

ITEM	ORDER CODE	ITEM	ORDER CODE
Eyelid Cover White	283099	MW Sensor Kit	283059
Emergency Kit	283049		

