

# SMART LIGHT | CEILING LIGHTING

2015036101

nordlux®



Voltage (V): 230 Volt  
IP degree if the fixture includes  
two types of IP degree: IP20  
Class (Class I, Class II, Class III):  
Class 2 (Double isolated)  
Lampholder type (eg, E27/E14,  
etc): LED Module

Primary material: Plastic

Width (cm): 29.4  
Length (cm): 29.4  
Projection (cm): 2.3  
EAN: 5704924002977  
TUN: 2116034  
Item Number: 2015036101  
Pcs Per Master Carton: 3  
Sales Box Height (cm): 30  
Sales Box Width(cm): 29.5

Sales Box Depth (cm): 2.8  
Sales Box Volume m<sup>3</sup> : 0.0025  
Net weight of the luminaire (kg):  
0.6

Useful Lumen (lm): 1600  
Color Temperature (K): 2700-  
6500  
Ra-value : 80  
Lifetime (h): 25000  
Spread Angle (°) (beam angle of  
luminaire): 120  
Candela (cd) (for directional  
lamp only): 0  
Energy Class: F

- Ultra-slim ceiling panel light • Bluetooth connection to Nordlux SmartLight
- Adjustable kelvin and lumen output • Ultra-slim ceiling panel light

Oja is an ultra slim ceiling panel light in a modern and simple design that is very easy to install and can be connected to Nordlux Smart Light using Bluetooth. With your chosen device you will have the ability to change the light from a warm white to a cool white.

Oja is integrated with the newest Bluetooth Mesh technology which allows you to control the light using your phone and that works both indoor and outdoor with a stable communication between your devices.