



FEATURES

- Plastic downlight with internal aluminium heat sink
- High efficiency SMD chips
- Constant current driver
- Opal polycarbonate diffuser
- IC-F and IC-4 rating. Can be installed under ceiling insulation
- Removable flex and plug
- 6mm terminals for hard wiring

DIMMING OPTIONS

- Trailing and Leading Edge
- Universal

INCLUDES

- Fixed head LED downlight
- Build-in dimmable LED driver
- 1.2 m flex and plug

APPLICATIONS

- Residential
- Hotels and shops
- Conference rooms
- Reception areas
- Bathrooms and wet areas

WARRANTY

- Five years (subject to terms and conditions)

CERTIFICATION			IP RATING	DIMMABLE	Ra	DISTRIBUTION	DIMENSIONS(mm)	

Part No.	Voltage	Watt.	PF	Color Temp.	Lumens	Beam Angle	Lifetime L70B50	Diffuser	Net Weight (kg)
172031A	220-240V	9W	0.9	3000K	750lm	100°	35000h	Flush	0.28
172032A	220-240V	9W	0.9	4000K	800lm	100°	35000h	Flush	0.28
172061A	220-240V	9W	0.9	5000K	800lm	100°	35000h	Flush	0.28
173083	220-240V	9W	0.9	3000K	750lm	100°	35000h	Recessed	0.26
173084	220-240V	9W	0.9	4000K	800lm	100°	35000h	Recessed	0.26
173085	220-240V	9W	0.9	5000K	800lm	100°	35000h	Recessed	0.26

Part No.	Model No.	VEET Status	IPART Status
172031A 172032A 172061A	YKRS3F5A-D 9W	Approved No.: 4914	Approved No.: 24143D15-K6EGGJ
173083 173084 173085	YKRS3F5B-D 9W	Approved No.: 5425	Approved No.: 24143D15-LQPIHHF

[1] Operating Frequency=50/60Hz;

[2] This fitting is IP54 only once installed;

[3] Operating Temperature:-10 °C~+40 °C

