



REFURBISHING?

Think

**WIDER  
LONGER**

**No More Ceiling Repainting  
In Retrofit Applications.**

**Benefits**

- Extra width and length in retrofit applications.
- 6mm terminal block and dual **25mm cable entry knockouts** and **multiple back entry holes** for easy wiring.
- Modular tool less design saves installation time and effort.
- Insect-free LED module.

# Stellar V Wide

Indoor Wide-body Batten



2FT 640x130X80mm (LxWxH)

4FT 1240x130X80mm (LxWxH)

Order Code*	Features	Multi-Wattage	CCT	Lumen Output
211025	2ft, Flicker-Free, CRI 80	10/14/20W	3/4/5/5.7/6.5K	900-2000Lm
211025DS	2ft Microwave Dimming Sensor, CRI 80	10/14/20W	3/4/5/5.7/6.5K	900-2000Lm
211025EM	2ft, Flicker-Free, CRI 80	10/14/20W	3/4/5/5.7/6.5K	900-2000Lm
211025DEMS	2ft Microwave Dimming Sensor, CRI 80	10/14/20W	3/4/5/5.7/6.5K	900-2000Lm
211026	4ft, Flicker-Free, CRI 80	10-40W**	3/4/5/5.7/6.5K	900-4000Lm
211026DS	4ft Microwave Dimming Sensor, CRI 80	10-40W**	3/4/5/5.7/6.5K	900-4000Lm
211026EM	4ft, Flicker-Free, CRI 80	10-40W**	3/4/5/5.7/6.5K	900-4000Lm
211026DEMS	4ft Microwave Dimming Sensor, CRI 80	10-40W**	3/4/5/5.7/6.5K	900-4000Lm

\*DS: Microwave Dimming Sensor. EM: Emergency. DEMS: Emergency & Microwave Dimming Sensor.

\*\* 10/14/20/24/26/30/36/40W

**QUALITY • INNOVATION • CONVENIENCE**



**ORDER NOW**

**CALL 1300 215 598**

1/350 Edgar Street, Condell Park, NSW 2200 Australia

[EnergeticLighting.com.au](http://EnergeticLighting.com.au) [sale@energeticlighting.com.au](mailto:sale@energeticlighting.com.au)